

CLAIMS:

We claim:

1. An acoustic blanket, comprising:

a first carbon Teflon impregnated fiberglass cover material;

5 a second carbon Teflon impregnated fiberglass cover material heat-sealed to the first cover material around at least a portion of a perimeter of the first and second cover materials; and

at least one Polyimide foam panel disposed between the heat-sealed first and second cover materials.

2. The blanket of Claim 1 comprising:

a plurality of fastener assemblies to connect the acoustic blanket to a structure so as to define an air gap of pre-determined dimension between the acoustic blanket and the structure, wherein the pre-determined dimension of the air gap is controllable by the fastener assemblies.

3. The blanket of Claim 1 comprising:

at least one vent disposed in at least one of the first and second cover materials.

20 4. The blanket of Claim 3 wherein the at least one vent comprises:

one of a stainless steel vent screen and a Teflon vent screen heat-sealed into the at least one of the first and second cover materials.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

5. The blanket of Claim 1 comprising:
a plurality of Polyimide foam panels disposed between the heat-sealed first and second cover materials.

5 6. The blanket of Claim 1 comprising:
at least one barrier ply layer disposed between the heat-sealed first and second cover materials.

7. The blanket of Claim 6 wherein the at least one barrier ply layer comprises:
one of a butyl rubber layer and a silicon rubber layer.

8. The blanket of Claim 6 wherein the at least one barrier ply layer comprises:
a carbon Teflon impregnated fiberglass layer.

9. The blanket of Claim 2 comprising:
a plurality of grommets disposed in the heat-sealed perimeter of the first and second cover materials.

10. The blanket of Claim 9 wherein the plurality of fastener assemblies comprise:
20 a plurality of standoffs mounted on the structure and collocated with the plurality of grommets; and

a plurality of members threadable into the plurality of standoffs to secure the acoustic blanket to the standoffs and position the blanket above the structure so as to define the pre-determined air gap between the acoustic blanket and the structure.

5 11. The system of Claim 1 wherein the acoustic blanket weight is in the range of one-quarter pound per square foot and one pound per square foot.

12. An acoustic blanket system, comprising:

a first cover material;

a second cover material connected to the first cover material;

at least one acoustic attenuating panel disposed between the first and second cover materials; and

a plurality of fastener assemblies to connect the acoustic blanket to a structure so as to define an air gap of pre-determined dimension between the acoustic blanket and the structure, wherein the fastener assemblies control the pre-determined dimension of the air gap.

13. The blanket of Claim 12 comprising:

at least one vent screen disposed in at least one of the first and second cover

20 materials.

14. The blanket of Claim 13 wherein the at least one vent comprises:

one of a stainless steel vent screen and a Teflon vent screen heat-sealed in the at least one of the first and second cover materials.

5

15. The blanket of Claim 12 wherein the at least one acoustic attenuating panel comprises:

a Polyimide foam panel.

10 16. The blanket of Claim 12 comprising:

a plurality of acoustic attenuating panels disposed between the first and second cover materials.

15 17. The blanket of Claim 16 comprising:

at least one barrier ply layer disposed between the first and second cover materials.

18. The blanket of Claim 12 wherein the first and second cover materials comprise:

carbon Teflon impregnated fiberglass, and wherein the first and second cover materials are heat-sealed around at least a portion of a perimeter of the first and second cover materials and include a plurality of grommets disposed within the heat-sealed perimeter.

19. The blanket of Claim 18 wherein the plurality of fastener assemblies comprise:
a plurality of standoffs mounted on the structure and collocated with the plurality
of grommets; and

a plurality of members threadable into the plurality of standoffs to secure the
5 acoustic blanket to the standoffs so as to define the pre-determined air gap between the
acoustic blanket and the structure.

20. An acoustic blanket system for space vehicles, comprising:

a structure defining at least a portion of a space vehicle;

at least one acoustic blanket connected to the structure comprising:

a first Teflon impregnated fiberglass cover material;

a second Teflon impregnated fiberglass cover material heat-sealed to the
first cover material around at least a portion of the perimeter of the first and
second cover material;

at least one Polyimide foam panel disposed between the heat-sealed first
and second cover materials; and

a plurality of fastener assemblies to connect the acoustic blanket to the
structure.

20 21. The system of Claim 20 wherein the plurality of fastener assemblies connect the
acoustic blanket to the structure to define an air gap of pre-determined dimension
between the acoustic blanket and the structure, wherein the fastener assemblies control
the pre-determined dimension of the air gap.

27. The blanket of Claim 26 wherein the plurality of fastener assemblies comprise:
a plurality of standoffs mounted on the structure and collocated with the plurality
of grommets; and

5 a plurality of members matable with the plurality of grommets and threadable into
the plurality of standoffs to secure the acoustic blanket to the standoffs so as to define
the pre-determined air gap between the acoustic blanket and the structure.

28. A method for constructing an acoustic blanket, the method comprising:
providing first and second cover materials comprising Teflon impregnated
fiberglass;

providing a Polyimide foam panel of a pre-determined dimension; and

heat-sealing a perimeter of the first and second cover materials with the
Polyimide foam panel disposed within a cavity defined by the heat-sealed first and
second cover material.

29. The method of Claim 28 wherein the step of heat-sealing comprises:
disposing a plurality of grommets within the perimeter of the first and second
cover materials.

30. The method of Claim 28 comprising:
providing at least one vent; and
heat-sealing the at least one vent into one of the first and second cover material.

31. The method of Claim 28 comprising:

providing a plurality of Polyimide foam panels; and

heat-sealing the perimeter of the first and second cover materials with the plurality of the Polyimide panels disposed within the cavity.

5

32. The method of Claim 31 comprising:

providing at least one barrier ply layer; and

heat-sealing a perimeter of the at least barrier ply layer into the perimeter of the first and second cover materials.

33. A method of mounting an acoustic blanket to a structure, the method comprising:

connecting a plurality of standoffs to the structure so that individual ones of the plurality of standoffs are collocated with an individual one of a plurality of apertures in the perimeter of the acoustic blanket;

passing an individual one of a plurality of fasteners through the individual apertures; and

connecting the individual fasteners to the individual standoffs to secure the acoustic blanket to the plurality of standoffs

20